


## PDF technical sheet 22205EG15W33C3




### Double row spherical roller bearings

Spherical roller bearing, polyamide cage, groove and lubrication holes on outer ring

| Product definition          |          |
|-----------------------------|----------|
| d                           | 0.9843 " |
| D                           | 2.0472 " |
| B                           | 0.7087 " |
| d2                          | 1.2008 " |
| D1                          | 1.7913 " |
| rs min                      | 0.0394 " |
| Number of lubrication holes | 3        |
| b                           | 0.1181 " |
| k                           | 0.0591 " |
| e                           | 0.34     |
| Y1                          | 2        |
| Y2                          | 2.98     |
| Y0                          | 1.96     |
| Radial clearance class      | C3       |
| Mass                        | 0.58 oz  |
| Brand                       | SNR      |



| Product performance                           |            |
|-----------------------------------------------|------------|
| Dynamic load, C                               | 57.30 kN   |
| Static load, C0                               | 46.10 kN   |
| Fatigue limit load, Cu                        | 4.70 kN    |
| Nref                                          | 13,000 RPM |
| Nlim                                          | 17,000 RPM |
| Min operating temperature, Tmin               | -4 °C      |
| Max operating temperature, Tmax               | 248 °C     |
| Characteristic cage frequency, FTF            | 0.40 Hz    |
| Characteristic rolling element frequency, BSF | 4.85 Hz    |
| Characteristic outer ring frequency, BPF0     | 5.65 Hz    |
| Characteristic inner ring frequency, BPF1     | 8.36 Hz    |



### Abutment dimensions

|        |          |
|--------|----------|
| da min | 1.2047 " |
| Da max | 1.8268 " |
| ra max | 0.0394 " |

### Calculation factors

#### Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

| Fa / Fr ≤ e |    | Fa / Fr > e |    |
|-------------|----|-------------|----|
| X           | Y  | X           | Y  |
| 1           | Y1 | 0.67        | Y2 |

#### Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

| X <sub>0</sub> | Y <sub>0</sub> |
|----------------|----------------|
| 1              | Y0             |

The values for e, Y1, Y2 and Y0 are shown in the above table .