



- Edelstahl 1.4408 -

Arbeitsdruck:
Innengewinde:
Außengewinde:

max. 20 bar
zylindrisch nach DIN EN ISO 228-1
zylindrisch nach DIN EN ISO 228-1



266.09-ES

Reduziernippel, 6-kant

Art.-Nr.	Außen- gewinde G	Innen- gewinde G	SW	L1	L2	S
266.01-ES	1/4	1/8	17	19,0	14,0	16,8
266.02-ES	3/8	1/8	21	20,0	14,0	20,7
266.03-ES	3/8	1/4	21	19,1	12,0	20,7
266.04-ES	1/2	1/4	26	22,5	16,0	25,6
266.05-ES	1/2	3/8	26	22,5	16,0	25,6
266.06-ES	3/4	3/8	31	25,5	17,0	30,4
266.07-ES	3/4	1/2	31	25,5	17,0	30,4
266.08-ES	1	1/2	38	29,2	20,0	37,8
266.09-ES	1	3/4	38	29,2	20,0	37,8
266.10-ES	1 1/4	3/4	46	30,0	21,0	45,4
266.11-ES	1 1/4	1	46	32,0	23,0	45,4
266.12-ES	1 1/2	1	53	32,0	23,0	52,9
266.13-ES	1 1/2	1 1/4	53	32,0	22,2	52,9
266.14-ES	2	1	63	37,0	26,0	62,5
266.15-ES	2	1 1/2	63	34,0	24,0	62,5