


PDF technical sheet 22211EMKW33C4




Double row spherical roller bearings

Spherical roller bearing, one-piece machined cage, groove and lubrication holes on outer ring, tapered bore 1:12

Product definition	
d	2.1654 "
D	3.9370 "
B	0.9843 "
D1	3.5315 "
rs min	0.0591 "
Number of lubrication holes	3
b	0.2520 "
k	0.1181 "
Associated sleeve reference	H311
e	0.23
Y1	2.95
Y2	4.39
Y0	2.89
Radial clearance class	C4
Mass	2.86 oz
Brand	SNR



Product performance	
Dynamic load, C	148 kN
Static load, C0	140 kN
Fatigue limit load, Cu	16.90 kN
Nref	6,100 RPM
Nlim	8,200 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	392 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.29 Hz
Characteristic outer ring frequency, BPF0	7.20 Hz
Characteristic inner ring frequency, BPF1	9.81 Hz



Abutment dimensions

da min	2.5197 "
Da max	3.5827 "
ra max	0.0591 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X ₀	Y ₀
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .